Ref No: BPR-IK-3X2139 Date: 23-AUG-2019

Author: EP, JB, VK. Version: 2



Bioprinting Protocol

GelXA FIBRIN

This is a suggested procedure, please adjust according to your experimental needs.

Protocol aim

The aim of this protocol is to provide instructions for bioprinting with the GelXA FIBRIN bioink using the INKREDIBLE, INKREDIBLE+, or BIO X, with and without cells. This document covers pre-print mixing with cells, 3D bioprinting and post-print processes of crosslinking ionically or through photocuring. This protocol was optimized for GelXA FIBRIN with LAP 0.25% undiluted as well as a 10+1 cell suspension dilution. Changing the concentration of LAP or bioink to cell suspension ratio will change the photocrosslinking time. Reference the Photocrosslinking Optimization Protocol to adjust and determine these numbers. This protocol was optimized using the pneumatic printhead using the BIO X.

Materials needed

- GelXA FIBRIN bioink*
- UV shielding cartridges, 3cc*
- Sterile conical bioprinting nozzles, 22-27G*
- BIO X or INKREDIBLE-series 3D Bioprinter*
- Well plate or Petri dish*
- 405/365 nm light modules for photocuring
- Crosslinking Agent (included with the bioink purchase)
- Vial with 100 U thrombin (included with the bioink purchase)
- Cells + cell culture medium
- 3 mL syringes with Luer lock connections
- Female/female Luer lock adaptor*
- CFLLMIXFR*

*The products can be purchased in the CELLINK store at www.cellink.com/store/.

KEEP THE BIOINK PROTECTED FROM LIGHT IF TRANSFERRED FROM THE ORANGE UV PROTECTED CARTRIDGES TO AVOID CROSSLINKING BEFORE PRINTING. WORK WITH 3D PRINTERS IN DARK MODE. THE PHOTOINITIATOR IS SENSITIVE TO REPEATED OR PROLONGED EXPOSURE TO HEAT.

Boston, USA 75 Kneeland Street Boston, MA 02111

Gothenburg, Sweden Arvid Wallgrens Backe 20, Gothenburg, 41346

Blacksburg, USA Blacksburg, VA 24060

Kyoto, Japan 2000 Kraft Dr, Suite 2125 46-29 Yoshida-Shimo Adachicho, Sakyo-ku, Kyoto

Protocol

This protocol works best using the BIO X with the cooled print bed. If using the INKREDIBLE series, the printing substrates such as Petri dishes or well plates should be placed on ice or another cooled surface to thermally gel the construct after printing prior to photocrosslinking.

Step	Title	Material	Description	
1	Prepare	- GelXA FIBRIN	If not printing with cells move directly to step 3.	
	bioink		 Heat up GeIXA FIBRIN in a cartridge to 33-37°C. The heating of the GeIXA FIBRIN can be performed in a pneumatic printhead, water bath or incubator. 	
			Note: If there are bubbles in the bioink, make a quick centrifugation for 1.5 min at 1600 rpm.	
2	Mix GelXA FIBRIN with cells	- Cell suspension - CELLMIXER - Female/female	At this point, mix ten parts of bioink with one part of cell suspension, taking care not to introduce air bubbles to the mixture. For detailed instructions see the Mixing Cells Protocol GelX Series.	
		Luer lock adaptor - 3 mL syringes with Luer lock connections - Prewarmed GeIXA FIBRIN	 Transfer the cell suspension to the 1 mL cell syringe (PART 1) using a female/female Luer lock adaptor. 	
	C		connections - Prewarmed	- Transfer GelXA FIBRIN to the 12 mL syringe (PART 2) using a female/female Luer lock adaptor.
				- Clip both syringes to the dispensing unit (PART 3).
				- Connect the two syringes to the mixing unit (PART 4), then connect the empty cartridge (PART 5) to the mixing units from another side.
			 Apply gentle pressure onto the dispensing unit to mix the content of both syringes into the empty cartridge. 	
			Note: To avoid an air gap when mixing the bioink and the cell suspension, carefully pre-fill the Luer lock adaptor with GeIXA FIBRIN before attaching the syringe with the cell suspension.	
			If preparing for quantities <2 ml of GelXA FIBRIN, it is recommended to connect two 3 mL Luer lock syringes and mix the bioink back and forth between the syringes until it becomes homogeneous.	
3	Cool and load the	- UV shielding cartridges, 3cc loaded with	- Place cartridge on counter for 20 min to reach room temperature.	
	cartridge	TOUGED WILL	Note: Room temperature is within 20-25°C.	

Boston, USA 75 Kneeland Street Boston, MA 02111

Gothenburg, Sweden Arvid Wallgrens Backe 20, Gothenburg, 41346

Blacksburg, USA Blacksburg, VA 24060

Kyoto, Japan 2000 Kraft Dr, Suite 2125 46-29 Yoshida-Shimo Adachicho, Sakyo-ku, Kyoto

			 Place the room tempered GelXA FIBRIN in the printhead and cap with the printing nozzle. If using the BIO X, pre-cool the print bed to 15°C. Note: When printing with GelXA FIBRIN, the recommended printhead temperature for the highest printing fidelity is 20-25°C, though the bioink can be dispensed up to 32°C.
4	Printing	- Bioprinter (BIO X or INKREDIBLE series	- Bioprint structures with parameters according to Table 1. If printability is not as desired, adjust the pressure up/down by 1 kPa to extrude more/less material.
		recommended) - Well plate or Petri dish	Note: If waiting too long between extrusions the bioink can dry in the nozzle causing it to clog. If this occurs, replace with new nozzle.

Table 1. Recommended minimal extrusion pressure* (±2 kPa) used for printing continuous filaments at 20-25°C with cells/without cells. 'With cells' assumes a mixture of one part of cell suspension to ten parts of bioink. For highly concentrated cell suspensions, the pressure needs to be increased towards the pressure used for undiluted bioink.

Printing speed (mm/s) \rightarrow Nozzle size (G) \downarrow	5	10	15	20
22	15 28	20 34	22 37	24 38
25	21 34	25 42	31 48	33 53
27	19 55	25 65	32 72	35 81

*Note: This is only a recommended reference of starting pressures. The actual pressure needed will vary depending on the preparation procedures (amount of bioink and actual temperature of the bioink) as well as the fitting of the piston in the cartridge and the leveling of the print surface. This table was generated with printhead temperature of 24°C and with a bioink dilution with a low concentration of cells.

Step	Title	Material	Description
5	Crosslinking	Agent AND/OR	GelXA FIBRIN can be photocrosslinked using the 405 or 365 nm light modules or ionically crosslinked using the CaCl ₂ -containing Crosslinking Agent with thrombin. If using both, begin with photocrosslinking.
		- 405/365 nm light modules for photocuring - Cell culture medium	 Photocrosslinking: see Table 2 below for recommended crosslinking times. Ensure that the bioprinted GelXA FIBRIN construct is thermally gelled after printing by cooling the print bed (if using the BIO X) or placing the printing substrates with the construct on ice for 10 s (if using the INKREDIBLE series). If photocrosslinking during bioprinting, set the crosslinking parameters

Boston, USA 75 Kneeland Street Boston, MA 02111 Gothenburg, Sweden Arvid Wallgrens Backe 20, Gothenburg, 41346 Blacksburg, USA 2000 Kraft Dr, Suite 2125 Blacksburg, VA 24060 Kyoto, Japan 46-29 Yoshida-Shimo Adachicho, Sakyo-ku, Kyoto appropriately in the G-code for the INKREDIBLE series or the printhead setup page for the BIO X.

Note: It is recommended to use the 405 nm light module instead of 365 nm one if possible. Overexposure might damage the cells.

Note: To verify the crosslinking is sufficient, add 37°C media to one printed well and observe that it doesn't dissolve.

Ionic crosslinking: 1) Prepare 10 mL of thrombin crosslinking solutions (10 U/mL) by adding 1 mL of crosslinking solution to the thrombin vial. Then transfer 1 mL of thrombin solution to 9 mL of crosslinking solution. Mix gently by pipetting up and down 2-3 times. 2) Submerge the cell-laden constructs in the crosslinking solution for 30 s to 5 min depending on construct size. Remove crosslinking solution and rinse constructs with basal culture media once.

Table 2. Recommended time of the construct photocrosslinking**. Distance from each light module to construct was set to 5 cm using the BIO X photocuring modules. If using the INKREDIBLE series photocuring modules, the time required can possibly be decreased. For crosslinking with other parameters, see Photocrosslinking Optimization Protocol. This table was generated using GelXA FIBRIN with mesenchymal stem cells. Don't exceed the exposure time to more than 120 s when printing with cells.

	365 nm, LAP 0.25%	405 nm, LAP 0.25%
Construct donth (mm) (time (c)	1/5	1/10
Construct depth (mm) /time (s)	3/15	3/30

^{**}Note: This is only a recommended reference of crosslinking times to start with. The actual time needed for crosslinking will vary depending on the size and temperature of the constructs as well as the intensity of the photocuring module and the distance to the construct.

Step	Title	Material	Description
6	Incubation	- Cell culture medium	 After crosslinking, add the desired medium to the constructs and place them in an incubator.
			 Incubate the constructs in cell culture medium in standard culture conditions (37°C, 5% CO₂ and 95% relative humidity) or according to your application.